



型式 MODEL	全容量 VOLUME	操作量 CAPACITY	主動力 MAIN POWER	副動力 SCREW POWER	外型尺寸 DIMENSIONS(m/m)			重量 WEIGHT
					D	H1	H2	
NX-6	1300 liter	600 liter	7-1/2HP-6P	- - -	1500	2265	3265	1150kgs
NX-10	2100 liter	1000 liter	7-1/2HP-6P	- - -	1700	2635	4025	1250kgs
NX-15	3000 liter	1500 liter	10HP-4P	2HP-1/29	1920	2985	3630	1350kgs
NX-20	4000 liter	2000 liter	10HP-4P	2HP-1/29	2080	3265	4300	1450kgs
NX-30	6000 liter	3000 liter	15HP-4P	2HP-1/29	2360	3760	4800	2450kgs
NX-40	8000 liter	4000 liter	20HP-4P	2HP-1/29	2765	4485	5785	2650kgs
NX-50	10000 liter	5000 liter	25HP-4P	3HP-1/43	2920	4765	6065	3100kgs
NX-60	12000 liter	6000 liter	25HP-4P	3HP-1/43	3060	5420	6720	3300kgs
NX-70	14000 liter	7000 liter	25HP-4P	3HP-1/43	3185	5235	6535	3550kgs
NX-100	18500 liter	10000 liter	30HP-4P	3HP-1/43	3500	5780	7080	3900kgs

特性

- 利用螺旋葉自轉及公轉之原理可迅速混合。
- 攪拌均勻混合效果佳。
- 混合過程中粉體不易損壞。
- 所需動力小。
- 排料容易無死角。
- 保養容易清洗方便。
- 夾套可依操作所需改為半邊管。

用途

- 醫藥品、特化品、食品、染料、顏料、樹脂、飼料等。

features

- Tapered screw that revolving and rotating decreases the blending time.
- Improving the efficiency of the blender.
- Blending without damaging the particle geometry of powder and granules.
- Discharging without dead corner
- Maintenance and cleaning convenience.
- Jacket design can be change to half tubes upon request.

application

- Pharmaceuticals, fine chemicals, food, dyestuff pigments, resin and feedstuff, etc.